

A-level PHYSICS (7408/1)

Paper 1

Mark scheme v1.1

Specimen paper

Mark schemes are prepared by the Lead Assessment Writer and considered, together with the relevant questions, by a panel of subject teachers. This mark scheme includes any amendments made at the standardisation events which all associates participate in and is the scheme which was used by them in this examination. The standardisation process ensures that the mark scheme covers the students' responses to questions and that every associate understands and applies it in the same correct way. As preparation for standardisation each associate analyses a number of students' scripts. Alternative answers not already covered by the mark scheme are discussed and legislated for. If, after the standardisation process, associates encounter unusual answers which have not been raised they are required to refer these to the Lead Assessment Writer.

It must be stressed that a mark scheme is a working document, in many cases further developed and expanded on the basis of students' reactions to a particular paper. Assumptions about future mark schemes on the basis of one year's document should be avoided; whilst the guiding principles of assessment remain constant, details will change, depending on the content of a particular examination paper.

Further copies of this mark scheme are available from aga.org.uk

Physics - Mark scheme instructions to examiners

1. General

The mark scheme for each question shows:

- the marks available for each part of the question
- the total marks available for the question
- the typical answer or answers which are expected
- extra information to help the Examiner make his or her judgement and help to delineate what
 is acceptable or not worthy of credit or, in discursive answers, to give an overview of the area
 in which a mark or marks may be awarded.

The extra information is aligned to the appropriate answer in the left-hand part of the mark scheme and should only be applied to that item in the mark scheme.

At the beginning of a part of a question a reminder may be given, for example: where consequential marking needs to be considered in a calculation; or the answer may be on the diagram or at a different place on the script.

In general the right-hand side of the mark scheme is there to provide those extra details which confuse the main part of the mark scheme yet may be helpful in ensuring that marking is straightforward and consistent.

2. Emboldening

- 2.1 In a list of acceptable answers where more than one mark is available 'any **two** from' is used, with the number of marks emboldened. Each of the following bullet points is a potential mark.
- 2.2 A bold **and** is used to indicate that both parts of the answer are required to award the mark.
- 2.3 Alternative answers acceptable for a mark are indicated by the use of **or**. Different terms in the mark scheme are shown by a /; eg allow smooth / free movement.

3. Marking points

3.1 Marking of lists

This applies to questions requiring a set number of responses, but for which candidates have provided extra responses. The general principle to be followed in such a situation is that 'right + wrong = wrong'.

Each error / contradiction negates each correct response. So, if the number of errors / contradictions equals or exceeds the number of marks available for the question, no marks can be awarded.

However, responses considered to be neutral (often prefaced by 'Ignore' in the mark scheme) are not penalised.

3.2 Marking procedure for calculations

Full marks can usually be given for a correct numerical answer without working shown unless the question states 'Show your working'. However, if a correct numerical answer can be evaluated from incorrect physics then working will be required. The mark scheme will indicate both this and the credit (if any) that can be allowed for the incorrect approach.

However, if the answer is incorrect, mark(s) can usually be gained by correct substitution / working and this is shown in the 'extra information' column or by each stage of a longer calculation.

A calculation must be followed through to answer in decimal form. An answer in surd form is never acceptable for the final (evaluation) mark in a calculation and will therefore generally be denied one mark.

3.3 Interpretation of 'it'

Answers using the word 'it' should be given credit only if it is clear that the 'it' refers to the correct subject.

3.4 Errors carried forward, consequential marking and arithmetic errors

Allowances for errors carried forward are likely to be restricted to calculation questions and should be shown by the abbreviation ECF or *conseq* in the marking scheme.

An arithmetic error should be penalised for one mark only unless otherwise amplified in the marking scheme. Arithmetic errors may arise from a slip in a calculation or from an incorrect transfer of a numerical value from data given in a question.

3.5 Phonetic spelling

The phonetic spelling of correct scientific terminology should be credited (eg fizix) **unless** there is a possible confusion (eg defraction/refraction) with another technical term.

3.6 Brackets

(....) are used to indicate information which is not essential for the mark to be awarded but is included to help the examiner identify the sense of the answer required.

3.7 Ignore / Insufficient / Do not allow

'Ignore' or 'insufficient' is used when the information given is irrelevant to the question or not enough to gain the marking point. Any further correct amplification could gain the marking point.

'Do **not** allow' means that this is a wrong answer which, even if the correct answer is given, will still mean that the mark is not awarded.

3.8 Significant figure penalties

An A-level paper may contain up to 2 marks (1 mark for AS) that are contingent on the candidate quoting the **final** answer in a calculation to a specified number of significant figures (sf). This will generally be assessed to be the number of sf of the datum with the least number of sf from which the answer is determined. The mark scheme will give the range of sf that are acceptable but this will normally be the sf of the datum (or this sf -1).

3.9 Unit penalties

An A-level paper may contain up to 2 marks (1 mark for AS) that are contingent on the candidate quoting the correct unit for the answer to a calculation. The need for a unit to be quoted will be indicated in the question by the use of 'State an appropriate SI unit for

your answer '. Unit answers will be expected to appear in the most commonly agreed form for the calculation concerned; strings of fundamental (base) units would not. For example, 1 tesla and 1 weber/metre² would both be acceptable units for magnetic flux density but 1 kg $\rm m^2~s^{-2}~A^{-1}$ would not.

3.10 Level of response marking instructions.

Level of response mark schemes are broken down into three levels, each of which has a descriptor. The descriptor for the level shows the average performance for the level. There are two marks in each level.

Before you apply the mark scheme to a student's answer read through the answer and annotate it (as instructed) to show the qualities that are being looked for. You can then apply the mark scheme.

Determining a level

Start at the lowest level of the mark scheme and use it as a ladder to see whether the answer meets the descriptor for that level. The descriptor for the level indicates the different qualities that might be seen in the student's answer for that level. If it meets the lowest level then go to the next one and decide if it meets this level, and so on, until you have a match between the level descriptor and the answer. With practice and familiarity you will find that for better answers you will be able to quickly skip through the lower levels of the mark scheme.

When assigning a level you should look at the overall quality of the answer and not look to pick holes in small and specific parts of the answer where the student has not performed quite as well as the rest. If the answer covers different aspects of different levels of the mark scheme you should use a best fit approach for defining the level and then use the variability of the response to help decide the mark within the level. i.e. if the response is predominantly level 2 with a small amount of level 3 material it would be placed in level 2.

The exemplar materials used during standardisation will help you to determine the appropriate level. There will be an answer in the standardising materials which will correspond with each level of the mark scheme. This answer will have been awarded a mark by the Lead Examiner. You can compare the student's answer with the example to determine if it is the same standard, better or worse than the example. You can then use this to allocate a mark for the answer based on the Lead Examiner's mark on the example.

You may well need to read back through the answer as you apply the mark scheme to clarify points and assure yourself that the level and the mark are appropriate.

Indicative content in the mark scheme is provided as a guide for examiners. It is not intended to be exhaustive and you must credit other valid points. Students do not have to cover all of the points mentioned in the indicative content to reach the highest level of the mark scheme

An answer which contains nothing of relevance to the question must be awarded no marks.

Question	Answers	Additional Comments/Guidance	Mark
01.1	95 protons ✓		1
	241 – 95 = 146 neutrons ✓		1
01.2	Beta minus decay. ✓	Marks can be given for a correct equation	1
	There is no change in the number of nucleons.	Ignore omitted antineutrino.	
	The number of protons increases by 1.✓		1
01.3	$ \begin{array}{cccccccccccccccccccccccccccccccccccc$		1
	Nucleon number = A = 241 − 4 = 237 ✓		1
	Proton number = Z = 95 −2 = 93 ✓		1
01.4	lonisation is the removal (or addition) of electrons from (to) an atom or molecule ✓		1

01.5	Only a small quantity of material is needed ✓		1
	The particles it emits do not travel more than a few centimetres ✓	Alternative for 2 nd mark: Would be stopped before reaching the outside of the detector	1
02.1	P at the end of linear section ✓		1
02.2	Measure original length and diameter ✓	Alternative:	1
	Determine gradient of linear section to obtain F /extension \checkmark $E = \frac{F}{e} \times \frac{length}{\pi \left(\frac{d}{2}\right)^2} \checkmark$	Convert to stress–strain graph and determine gradient.	1 1
02.3	Line from A Parallel to straight section of original Ending at horizontal axis ✓		1
02.4	Plastic deformation has produced permanent extension/re-alignment of bonds in material hence intercept non-zero√		1
	Gradient is same because after extension identical forces between bonds✓		1

02.5	0.2% is a strain of 0.002		
	Stress = 2.0 x 10 ¹¹ x 0.002 =		1
	4 x 10 ⁸ ✓		
	Force $(=\frac{\pi(6\times10^{-3})^2}{4}\times4\times10^8)$ ✓		1
	= 11.3 kN✓		1
02.6	Maximum force = 11300 N		
	Weight of mass = 600 x 9.81 = 5886 N✓		1
	Accelerating force must be less than		
	11300 − 5886 = 5423 N✓		1
	a (= F/m = 5423/600)		
	$= 9.0 \text{ m s}^{-2} \checkmark$		1
02.7	To lift double the load at the same acceleration, would require double the force, ✓	The first mark is for discussing the effect on the force	1
	To produce the same strain either use:	The other two are for discussing the two	,
	 double the cross-sectional area of the wire/increase the diameter by √2 – so the stress stays the same and therefore the strain is the same for the same wire, ✓ a wire with double the Young modulus – so that double the 	alternative methods of keeping the strain the same	1
	stress produces the same strain for the same diameter. ✓		1

03.1	$I_3 = I_1 + I_2 \checkmark$		1
03.2	10 V✓		1
03.3	$I_2 = (12 - 10) / 10\checkmark$ = 0.2 A \checkmark	Allow ce for 10 V The first mark is for the pd The second is for the final answer	1
03.4	pd across R2 increases As R1 increases as pd = $I_1 R_1 \checkmark$ pd across R3 = 10 V – pd across R_1 Therefore pd across R_3 decreases \checkmark pd across R_2 = 12 – pd across R_3 Therefore pd across R_2 increases \checkmark	First mark is for identifying that pd across R1 increases (from zero). Second mark is for identifying that pd across R3 must decrease Third mark is for identifying that this means pd across R2 must increase	1 1 1
04.1	Max GPE of block = Mgh = $0.46 \times 9.81 \times 0.63$ = $2.84 \text{ J} \checkmark$ Initial KE of block = ½ Mv ² = 2.84 J Initial speed of block $v^2 = (2 \times 2.84)/0.46$ $v = 3.51 \text{ ms}^{-1} \checkmark$	The first mark is for working out the GPE of the block The second mark is for working out the speed of the block initially The third mark is for working out the momentum of the block (and therefore pellet)	1

	momentum lost by pellet = momentum gained by block = $Mv = 0.46 \times 3.51 = 1.61 \text{ kg m s}^{-1} \checkmark$ Speed of pellet = $1.58 / m = 1.58 / 8.8 \times 10^{-3}$ = 180 ms^{-1} (183) \checkmark	The final mark is for the speed of the pellet At each step the mark is for the method rather than the calculated answer Allow one consequential error in the final answer	1
04.2	As pellet rebounds, change in momentum of pellet greater and therefore the change in momentum of the block is greater ✓ Initial speed of block is greater ✓ (Mass stays the same) Initial KE of block greater ✓ Therefore height reached by steel block is greater than with wooden block ✓	Ignore any discussion of air resistance	1 1 1
04.3	Calculation of steel method will need to assume that collision is elastic so that change of momentum can be calculated ✓ This is unlikely due to deformation of bullet, production of sound etc.✓ And therefore steel method unlikely to produce accurate results		1 1

05.1	Core is transmission medium for em waves to progress (by total internal reflection) ✓	Allow credit for points scored on a clear labelled diagram.	1
	Cladding provides lower refractive index so that total internal reflection takes place ✓		1
	And offers protection of boundary from scratching which could lead to light leaving the core. ✓		1
05.2	Blue travels slower than red due to the greater refractive index Red reaches end before blue, leading to material pulse broadening ✓	The first mark is for discussion of refractive index or for calculation of time difference.	1
	Alternative calculations for first mark Time for blue = $d/v = d/(c/n)$ = 1200/(3 x 10 ⁸ / 1.467) = 5.87 x 10 ⁻⁶ s	The second mark is for the link to material pulse broadening	1
	Time for red = $d/v = d/(c/n)$		
	= $1200/(3 \times 10^8 / 1.459) = 5.84 \times 10^{-6} \text{ s}$ Time difference = $5.87 \times 10^{-6} - 5.84 \times 10^{-6} = 3(.2) \times 10^{-8} \text{ s}$		

05.3	Discussions to include: Use of monochromatic source so speed of pulse constant Use of shorter repeaters so that the pulse is reformed before significant pulse broadening has taken place. Use of monomode fibre to reduce multipath dispersion ✓ ✓	Answer must make clear that candidate understands the distinction between modal and material broadening.	2
06.1	Suitable experiment eg diffraction through a door/out of a pipe ✓		1
06.2	Using $c = d/t$ t = 2500/480 = 5.2 s		1
06.3	(Measured time is difference between time taken by light and time taken by sound) Calculation assumes that light takes no time to reach observer, ie speed is infinite ✓	Do not allow "could not know speed of light"	1
06.4	Sound from gun is a mixture of frequencies. ✓ All the sound reaches observer at the same time, ✓	Alternative for 1 st mark '(so speed is independent of frequency) the sound of the gun is similar when close and far away'	1 1
06.5	More accurate, as it is closer to the accepted value. ✓		1
06.6	When $\theta = 0$ °C c = 331.29 m s ⁻¹ Therefore 331.29 = k $\sqrt{273.15}$ \checkmark k = 20.045 \checkmark		1

	The method and value are published ✓	1
06.7	other scientists repeat the experiment using the same method ✓	1

_	_	•		40		40	40	4.4	4.5	40	4=	40	40
Q	7	8	9	10	11	12	13	14	15	16	17	18	19
A	С	D	В	С	В	С	В	С	В	D	Α	С	D
Q	20	21	22	23	24	25	2	26	27	28	29	30	31
Α	В	С	Α	Α	С	D		С	Α	С	С	С	D

