

- 1 (a) three valid features listed without explanation [1]

any three features explained from:

copper/metal is a good conductor (of heat)
NOT of electricity

black is good absorber/bad reflector
ignore emitter

insulating material will reduce heat lost/conducted away (from pipes/sheet)
NOT prevents heat loss owtte

glass/trapping of air reduces/prevents convection/warm air being blown away

glass produces greenhouse effect/reference to far and near I.R. [max 3]

- (b) 38 – 16 OR 22 [1]

$mc\theta$ OR $250 \times 4200 \times$ candidate's temperature difference [1]

2.31×10^7 (J) e.c.f. from previous line [1]

9.24×10^7 J OR e.c.f. from previous line $\times 4$ correctly evaluated [1]

no unit penalty if J seen anywhere in (b) clearly applied to an energy

- (c) valid explanation relating to at least one of the reasons below: [1]

note: if no explanation, this mark is not awarded even if more than three reasons are given

any three reasons from:

which direction roof faces

estimate output of panels

household needs / whether household will use all hot water

cost of panel / installation

time to recoup cost

whether roof is shaded

relevant environmental consideration (e.g. not using wood or other fuel to heat water) [max 3]

- (d) nuclei join together, accept hydrogen for nuclei [2]
to produce a different element / helium (and energy)



- 2 (a) (i) mention of vacuum OR glass is a poor conductor
OR vacuum/gap between walls has no molecules/atoms/particles B1
- (ii) surface/silver (of walls) is good reflector/poor absorber (of radiation) B1
surface/silver (of walls) is poor emitter (of radiation) B1
- (b) add a stopper/lid/bung/cover/top to reduce/prevent (loss of heat by) convection/
conduction/radiation/evaporation OR to prevent steam/hot vapour leaving M1
B1
- made of insulator OR example of insulator to reduce/prevent (loss of heat by)
convection/radiation/evaporation OR to prevent steam/hot air leaving B1
- [Total 6]**
-
- 3 (a) (i) heated air/warm air rises/moves up (not sideways) B1
- (ii) air (between plate and hands) is a poor conductor/does not conduct B1
- (b) left hand/palm (facing matt black side gets hotter)
OR hand facing matt black side (gets hotter) B1
matt black side is a better emitter/radiator (of heat than shiny side) B1
- (c) conduction takes place B1
copper a good conductor/conduction is rapid/heat flows to equalise temperature B1
- [Total: 6]**



- 4 (a) black can/B loses heat energy quicker/ cools faster M1
OR polished can loses heat energy slower/ cools slower
- black radiates/emits more OR polished radiates/emits less
ignore anything about absorption A1 [2]
- (b) any four from: B4
- viable experiment e.g. pour in water and measure temperature
ignore methods with external thermometers (for this point only)
- pour (hot) water into both cans to same level/same amount
- place thermometers in same position relative to each can/detail relating to stirring
- thermometers not touching the metal of can
- observe change of temperature
- correct detail of timing
- repeat readings [4]
- (ii) use tiles as lids M1
reduce convection/evaporation (to room) A1
- OR alternative method
put tiles under cans (M1)
reduce, ignore prevent, conduction (to bench) (A1)
- for both methods, ignore other modes of heat transfer, ignore place tiles around can [2]
- (c) black can/B M
- black absorbs (radiation) better, ignore anything about emission A1 [2]
- [Total: 10]**

- 5 (a) (i) (metals/they are) (good) conductors (of heat) B1 [1]
- (ii) (at hot end) molecules vibrate (more)
 or electrons identified as mechanism of conduction B1
- molecules collide with their neighbours
 or electrons move faster/have more energy B1
- energy/vibration passed on
 or electrons pass on energy/reach far end/free to move B1 [3]
- (b) determine mass of spoon (condone weigh provided word mass is used in answer) B1
 immerse spoon in water/liquid B1
 determine increase in volume/overflow B1
 $\rho = m/V$ or density = mass/volume B1 [4]
- [Total: 8]
- 6 (a) (i) current
- (ii) p.d. OR potential difference OR voltage B1
- Both required
- (b) $R = R_1 + R_2$ OR $1.2 + 3.6$ OR 4.8 (k Ω) C
 $I = 9.0 / 4.8 = 1.875$ (mA) OR $9.0/4800 = 1.875 \times 10^{-3}$ (A)
 Voltmeter reading = 6.75 V *Unit penalty applies A1
 OR
 Voltmeter reading = $[R_1 / (R_1 + R_2)] V$ (C1)
 $= [3.6 / (1.2 + 3.6)] \times 9.0$ (C1)
 $= 6.75$ V *Unit penalty applies (A1)
- (c) (In fire) temperature of thermistor rises and its resistance falls B1
 Current (through thermistor and relay coil) rises / flows B1
 OR voltage / p.d. across / of relay coil rises
Magnetic field of relay closes switch (and bell rings) B1 [7]
- *Apply unit penalty once onl